

**WHAT IS CLAIMED:**

-- 1. A handle assembly utilized attached on a driver tool along with the method of attaching the assembly to the driver-tool, the tool being of a genre already possessing a handle and a shank extending perpendicularly from the handle, the tool's handle being able to spin the tool's shank, the tool's shank being used as an-axis- perpendicularly-inserted-through-components-of-the-assembly for rotation of the assembly components, the assembly comprising two separate positioned, shaped, utilized, and functioning halves, a hand utilized, discretely independently-rotatable, driver shank's slip ring type hand-held-guide half, and a rotatable, hand-operated, driver-shank's, drive-means half referred to herein as a drive-wheel, both components structured and sized such that the distance from at lease one axially-parallel-outward-surface of the guide to axis of the guide is essentially the same as the distance from the overall axially parallel outward surface of the drive-wheel to axis of the drive-wheel, the driver-tool's shank being used as axis running perpendicularly through both components, and both components sized so that their widths, as placed in line on the shank as axis, are such that a hand is able to grasp the two components simultaneously, and the hand-held-guide's shank-parallel outward-surface is shaped to enable holding in position on the guide any one portion of a hand grasping on the-shank-parallel-outward-surface of the said guide, while the drive-wheel's shank-parallel-outward-surface is shaped for ease of being, simultaneously along with the holding of the guide by a one portion of a hand, intermittently gripped, held, spun, and released by the grasp of any second, remaining not utilized on the guide, portion of the same said hand; and additionally, the drive-wheel being a separately utilized and functioning half of the assembly, is shaped with bluntly curved surfaces substantially uniformly symmetrical about the axis of the wheel, so enabling the wheel to rotate within the grasp of the releasing, not-utilized-on-the-guide, second portion of the said hand, such that the, not-utilized-on-the-guide, second portion of the said hand is able to remain in position for gripping the drive-wheel, and yet also is able to

23 rotate about the drive-wheel near or lightly touching the drive-wheel's surface, due to anchoring  
24 through linkage with the said hand's first portion which remains utilizing the guide, the guide being  
25 in addition discretely independently free-to-be-spun; the assembly's method of attachment  
26 comprising, having the slip ring type hand-held-guide slipped into place "loosely discretely, axially-  
26.1 rotatably, girdling so as free from axially-rotatably-engaging the said tool's shank, the shank being  
26.2 used as axis for the guide's rotation by running perpendicularly through the guide, the guide  
26.3 linearly retained in the guide's location-on-the-shank, the location being adjacent-in-line-forward  
26.4 the drive wheel half the assembly, which-also-rings-the-shank, the guide thereby being nearer the  
26.5 shank's work end than the wheel, the guide being as, aforesaid girdling, is also being as discretely  
27-28 independently free-to-be-spun unlimited in distance and/or direction relative the driver's shank as  
29 axis for the spin and relative the assembly's drive-wheel as a separate utilized and functioning half  
30 of the assembly, the guide's attachment being by way of having the shank inserted perpendicularly  
30.1 through a bore, the bore larger in diameter than the shank and piercing through the guide", the  
31 shank inserted to a distance through the guide's bore so reward of in line with the shank's work  
32-34 end, and the assembly's method of attachment also comprising having the drive-wheel-half-the-  
34.1 assembly "ringing so as axially rotatably encircling, utilizing a manner of engaging to spin, the said  
35 tool's shank, the shank as being both perpendicularly running through the wheel and used as axis  
35.1 for the wheel's rotation", the wheel linearly retained in its location on the shank, the location being  
36 adjacent-in-line-reward the guide-half-the assembly and further away from the shank's work-end  
37-38 than the guide, which also-girdles-the-shank, the wheel thereby being forward the fore-portion of  
39 the tool's handle and nearer the fore-portion than the guide, the tool's handle extending from plus  
40-41 engaging with the shank's portion emanating from opposite-the-side-of-the-assembly-from-the-  
42 side-facing-the-shank's-work-end, the wheel being as, aforesaid-engaging, also being such that will  
42.1 spin the shank when spun while the guide is being such that will spin discretely independent the

42.2 wheel when spun, thus the driver's handle is in line rearward the drive-wheel, the drive-wheel is in  
43 turn, in line rearward the guide, and the guide is in turn, in line rearward the work end of the  
44 shank; and both the gripwheel halves, the guide and wheel, are attached advantageously positioned  
45 near enough each other between the fore-portion of the driver's handle and the driver-shank's  
46 work end, such that a single hand is able to simultaneously grasp both the guide and drive-wheel  
47 utilizing them as bilongitudinally supporting halves, and at least one retainer is placed, a retainer  
48 in front of the hand-held-guide's side which faces the shank's work end, the retainer to help retain  
49 the components in assembled operating position.

50 -- 2. A handle assembly as described in claim 3 for use on a driver-tool wherein the said drive-  
51 wheel half of said auxiliary handle is attached in accordance with the method of attachment  
51.1 described in claim 3 comprising having the guide "ringing so as axially rotatably encircling,  
52 utilizing a manner of engaging to spin the said tool's shank, the shank being as both  
52.1 perpendicularly running through the wheel and used as axis for the wheel's rotation", engages  
53 upon the shank by manner of ringing the shank to encircle fixed upon the shank.

54 -- 3. A handle assembly as described in claim 3 for use on a driver-tool wherein the said drive-  
55 wheel half of said auxiliary handle is attached in accordance with the method of attachment  
55.1 described in claim 3 comprising having the guide "ringing so as axially rotatably encircling,  
56 utilizing a manner of engaging to spin the said tool's shank, the shank being as both  
56.1 perpendicularly running through the wheel and used as axis for the wheel's rotation", engages  
56.2 upon the shank through linkage by way of a drive-train, the train's driving component being fixed  
57 to said drive-wheel and the train's driven component being ringing to encircle fixed upon the  
58 shank.

59 -- 4. A handle assembly as described in claim 3 for use on a driver-tool wherein the said slip

60 ring type hand-held-guide half of said assembly is attached in accordance with the method of  
60.1 attachment described in claim 3 comprising having the guide "loosely discretely, axially-rotatably,  
60.2 girdling so as free from axially-rotatably-engaging the said tool's shank, the shank being used as  
60.3 axis for the guide's rotation by running perpendicularly through the guide, the guide linearly  
60.4 retained in the guide's location on the shank, the location being adjacent-in-line-forward the drive  
60.5 wheel half the assembly, which also rings the shank, the guide thereby being nearer the shank's  
60.6 work end than the wheel, the guide being as, aforesaid girdling, also being discretely independently  
61-62 free-to-be-spun unlimited in distance and/or direction relative the driver's shank as axis for the  
62.1 spin and relative the assembly's drive-wheel as a separate utilized and functioning half of the  
63 assembly, the attachment being by having the shank inserted perpendicularly through a bore, the  
63.1 bore larger in diameter than the shank and piercing through the guide", does loosely girdle the  
64 shank by manner of having the guide loosely discretely girdling as immediate of the shank-  
65 inserted-through-said-bore-through-the-guide.

66 -- 5. A handle assembly as described in claim 3 for use on a driver-tool wherein the said slip  
67 ring type hand-held-guide half of said assembly is attached in accordance with the method of  
67.1 attachment described in claim 3 comprising having the guide "loosely discretely, axially-rotatably,  
67.2 girdling so as free from axially-rotatably-engaging the said tool's shank, the shank being used as  
67.3 axis for the guide's rotation by running perpendicularly through the guide, the guide linearly  
67.4 retained in the guide's location on the shank, the location being adjacent-in-line-forward the drive  
67.5 wheel half the assembly, which also rings the shank, the guide thereby being nearer the shank's  
67.6 work end than the wheel, the guide being as, aforesaid girdling, also being discretely independently  
68-69 free-to-be-spun unlimited in distance and/or direction relative the driver's shank as axis for the  
69.1 spin and relative the assembly's drive-wheel as a separate utilized and functioning half of the  
70 assembly, the attachment being by having the shank inserted perpendicularly through a bore, the

70.1 bore larger in diameter than the shank and piercing through the guide”, does loosely girdle the  
71 shank as by manner of having the guide loosely-discretely girdling upon another component  
72 inserted through the bore through said guide, the other component being in turn ringing to encircle  
72.1 the said shank, the shank being concentric both the other component and guide respectively, in  
72.2 turn, at the same location lengthwise relative the guide, the guide thus loosely discretely girdling-  
72.3 the-shank by way of loosely discretely girdling the other component.